

Required information for RVU in COMMISSION REGULATION (EU) No. 1254/2014 ANNEX IV

(a)	Supplier's name	MITSUBISHI ELECTRIC CORPORATION
(b)	Model name	LGH-35RVX-EP
(c)	SEC (kWh/(m ² .a))	Average -39.8 Cold -76.9 Warm -15.9
(d)	Declared typology	RVU,BVU
(e)	Type of drive	Multi-speed
(f)	Type of HRS	Recuperative
(g)	Thermal efficiency (%)	77.9
(h)	Maximum flow rate (m ³ /h)	350
(i)	Electric power input (kW)	0.14
(j)	Casing sound power level (dB)	48
(k)	Reference flow rate (m ³ /s)	0.07
(l)	Reference pressure difference (Pa)	90
(m)	SPI (W/(m ³ /h))	0.25
(n)	Control factor and typology	Local demand control
(o)	Maximum leakage rate (%)	10
(p)	Mixing rate of non-ducted	-
(q)	Visual filter warning	Filter maintenance sign is displayed on the dedicated remote controller. Refer to the Maintenance section in the instruction manual.
(r)	Instructions to install regulated supply/exhaust grilles for unidirectional ventilation	-
(s)	Internet address for disassembly instructions	http://erp.mitsubishielectric.eu/
(t)	Airflow sensitivity for non-ducted units	-
(u)	air tightness for non-ducted units	-
(v)	AEC (kWh/a)	Average: 2.12 Cold: 7.49 Warm:1.67
(w)	AHS (kWh primary energy/a)	Average 44.4 Cold 86.9 Warm 20.1

MITSUBISHI ELECTRIC CORPORATION

Manufactured by: MITSUBISHI ELECTRIC CORPORATION

TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

Importer in EU: MITSUBISHI ELECTRIC EUROPE B.V.

HARMAN HOUSE, 1 GEORGE STREET, UXBRIDGE, MIDDLESEX, UB8 1QQ, U.K.

Revise A: 01/April/2021

N20HHZA0042A



ENERG

енергия · ενεργεια




Model LGH-35RVX-EP



48
dB



350 m³/h



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

357PP0303